

## Emergency Luminaire

### SALUTEM - LED Recessed Emergency Luminaire

An LED recessed non-maintained emergency downlight designed to provide discrete and outstanding emergency illumination with long life LED and low standby power consumption.

#### Features and Benefits

- Single LED with D63 emergency classification
- Lithium Ion battery including integrated battery management system (BMS) to maximise battery life
- Complete with flex and plug for easy installation
- Versatile two-piece disc with both large (144mm) and small disc (85mm)
- Designed and manufactured in accordance to AS/NZS 2293



Part Number: SATLI		
Input	Operating Voltage	230V
	Frequency	50Hz
Output	LED Array	Single LED
	Light Source	LED
	Lifetime	50,000 hour LEDs
	Function	Non-Maintained
	Lumen Output (Emergency Mode)	250lm
	Power Consumption (LEDs)	7.4W
Battery	Type	Li-Ion
	Protection	Overcharge and low voltage disconnect
	Emergency Runtime	3 hours*
Physical	IP Classification	IP20
	Weight	0.55kg
	Dimensions - Lamp Disc (ØxH)	Outer disc: 144x28mm / Inner disc: 85x28mm
	Dimensions - Control Box (LxWxH)	111x42x25mm
	Construction	Disc: Flame Retardant PC & Aluminum Heat Sink Control Box: Flame Retardant PC
Installation	Mounting	Recessed
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	C0	D63
	C90	D63
	Standards	AS/NZS 2293, AS/NZS 60598, AS/NZS CISPR15
Intelligence	Sentinel	No
	WiNetRF	No
Warranty	Duration	Fitting: 3 Years / Battery: 2 Years

\*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
41511	Replacement Battery

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 – D63 (m)	11.5	13.2	14.8	16.5
C90 – D63 (m)	11.5	13.2	14.8	16.5

\*Refer to AS/NZ 2293 for complete spacing table.