

Exit and Emergency Luminaires

JLEDLP Jumbo Exit Luminaire

A Premium Lithium LED all-in-one jumbo exit. Suitable for larger areas and high ceilings. Supplied complete with all Running man decal variations.



Features and Benefits

- 40m viewing distance
- Sentinel Automatic Self-testing built-in as standard
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximise battery life
- LED technology for bright consistent & efficient light distribution
- Easy to install and remove for maintenance purposes
- Suitable for large areas or high ceilings
- Wall or Ceiling Mountable
- Maintained / Non-maintained mode of operation
- High temperature components for extended life
- Designed and tested to comply with AS/NZS 2293



JLEDLP		
Input	Operating Voltage / Frequency	230V / 50Hz
	Light Source	LED
	Function	Multimode
Output	Power Consumption (LEDs)	4W
	Type	LiFePO ₄
	Charger	Variable Current CV
Battery	Protection	Overcharge and Low Voltage Disconnect
	Emergency Runtime	2 hours*
	Emergency Runtime	2 hours*
Physical	IP Classification	IP20
	Weight	5.1kg
	Dimensions (LxHxW)	560x315x100mm
	Construction	Folded Sheet Metal & Polycarbonate
Installation	Mounting	Surface - Wall or Ceiling
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	C0	E6.3
	C90	D12.5
	Standards	AS/NZS 2293, AS/NZS 60598, AS/NZS CISPR15
Warranty	Duration	Fitting: 5 Years / Battery: 3 Years
Intelligence	Sentinel	In-built
	WiNetRF	Compatible

*Guaranteed to meet runtime requirements of AS2293 throughout warranty duration.

ACCESSORIES	DESCRIPTION
32621	Replacement battery

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 – E6.3 (m)	6.9	7.4	7.9	8.2
C90 – D12.5 (m)	11.0	11.4	11.8	12.1

*Refer to AS2293 for complete spacing table.