

Exit & Emergency Luminaires

SMXLP MultiBlade Exit

The MultiBlade Exit combines sleek design with excellent performance. The MultiBlade Exit can be mounted as ceiling, wall, side or recessed (with optional recess kit) making this a versatile option for a wide range of applications.

Features and Benefits

- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life
- In-built Sentinel Automatic Self-testing capability
- High output LEDs for bright consistent & efficient light distribution
- Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration
- Single and double sided "Running Man" decals included
- 24m viewing distance
- Mounting options - Wall mount, Ceiling mount, Side mount & Recessed mount (recess kit sold separately P/N: XLP-RK)
- Available in suspended option (P/N: SFXLP)
- Designed and manufactured in accordance to AS/NZS 2293



LiFePO₄W₄WER™



| SMXLP | | |
|---------------------|--|---|
| Input | Operating Voltage / Frequency | 230V / 50Hz |
| Output | Light Source | LED |
| | Function | Multi-mode |
| | Power Consumption (LEDs) | 2W |
| Battery | Type | LiFePO ₄ |
| | Charger | Variable current CV |
| | Protection | Charger overcharge and low voltage disconnect |
| | Emergency Runtime | 2 hours* |
| Physical | IP Classification | IP20 |
| | Weight | 1.2kg |
| | Dimensions (LxWxH) | 360x215x60mm |
| | Construction | ABS |
| Installation | Mounting | Wall, side, ceiling or recessed (kit sold separately) |
| | Recessed Ceiling Cutout | 385x70mm |
| Environment | Temperature / Relative Humidity | 0°C - 40°C / 0 - 95% |
| Conformance | C0 | D4.0 |
| | C90 | D5.0 |
| | Standards | AS/NZS 2293, AS/NZS 60598, AS/NZS CISPR15 |
| Intelligence | Sentinel | In-built |
| | WiNetRF | Compatible |
| Warranty | Duration | Fitting: 5 Years / Battery: 3 Years |

*Guaranteed to meet runtime requirements of AS/NZ 2293 within warranty period.

| ACCESSORY | DESCRIPTION |
|---------------|------------------------------|
| XLP-RK | Recess Kit |
| 31511B | Replacement batter for SMXLP |

| SPACING TABLE | MOUNTING HEIGHT (m) | | | |
|---------------------|---------------------|-----|-----|-----|
| NATA Classification | 2.1 | 2.4 | 2.7 | 3.0 |
| C0 – D4.0 (m) | 7.1 | 7.2 | 7.3 | 7.3 |
| C90 – D5.0 (m) | 7.8 | 8.0 | 8.1 | 8.2 |

*Refer to AS2293 for complete spacing table.